



DEX-TECH III-H

DEXRON III-H is a Automatic Transmission Fluid with the following properties:

Extremely high viscosity index

High load capacity, outstanding wear minimisation

Low pour point

No foaming

High thermal stability

Reliable friction coefficient characteristic

Unrivalled viscosity-temperature behaviour

Excellent oxidation stability

No adverse effect on standard sealing materials

Use instructions:

Automatic motor vehicle transmissions and torque converters

Hydrostatic transmissions

Power steering systems

Hydraulic systems

Observe manufacturer instructions!

Colour: red

Specification

Recommended application

General Motors Dexron III-H

MB 236.1 / 236.5 / 236.6 / 236.7

MAN 339 Typ Z1/V1

Ford Mercon

Allison C-4

Cat TO-2

Voith H55.6335.3x(G607)

Volvo 97341

ZF TE-ML 03D/0 4D/09/11/14A/17C

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**



Technical data	Unit	Test according	DEX-TECH III-H
density at 15°C	Kg/m ³	DIN EN ISO 12185	860
Flammable COC	°C	DIN ISO 2592	176
Pourpoint	°C	DIN ISO 3016	-48
Viscosity 40°C	mm ² /s	DIN 51562-1	36
Viscosity 100°C	mm ² /s	DIN 51562-1	7,5
VI		DIN ISO 2909	176

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**