



HYPOID EVOLUTION GEAR SAE 75W-90 GL5

HYPOID EVOLUTION GEAR SAE 75W-90-GL5 is a semi-synthetic low-viscosity gear oil for manual transmissions and highly-loaded axle drives.

HYPOID EVOLUTION GEAR SAE 75W-90-GL5 possesses various advantages compared to conventional gear oils:

- Outstanding cold drivability
- excellent thermal stability
- exalted coefficient of viscosity
- sublime shear stability
- avoidance of cold-scraping and effective noise dampening
- excellent corrosion protection
- Reduction of fuel consumption
- Elongation of oil change intervals
- low abrasion and thus elongated transmission lifespan

HYPOID EVOLUTION GEAR SAE 75W-90-GL5 is used to lubricate highly-loaded hypoid gearboxes with great offsets, as well as all-wheel-drives in manual, transfer, and intermediate transmissions of automotive and processing machines.

Specification

API GL-5

Recommended application

- MB 235.0
- MAN 342 Typ M-1
- ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B
- Volvo 97310

powered by Quality.

PROFI-CAR
MADE IN GERMANY



Technical data	Unit	Test according	HYPOID EVOLUTION GEAR SAE 75W-90 GL5
density at 15°C	Kg/m ³	DIN EN ISO 12185	875
Flammable COC	°C	DIN ISO 2592	198
Pourpoint	°C	DIN ISO 3016	-45
Viscosity 40°C	mm ² /s	DIN 51562-1	76
Viscosity 100°C	mm ² /s	DIN 51562-1	14
VI		DIN ISO 2909	190

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
 Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**