



DEX-TECH ATF DSG

With its stable friction characteristic DEX-TECH ATF DSG offers excellent wear protection on high and low temperatures. A very high viscosity index, outstanding viscosity temperature behaviour and an excellent ageing and oxidation stability characterize DEX-TECH ATF DSG. Sealing materials are not affected.

DEX-TECH ATF DSG is an all-purpose double clutch transmission oil. Do not mix with other gear oils. Do not use for automatic transmissions or continuously variable transmissions (CVT).

Please consider OEMs instructions!

Specification

Recommended application

VW / Audi TL 521 82

BMW DCTF-1 / FFL-4 / MTF-5

MB-Freigabe 236.21

PSA 9734.S2

Ford WSS-M2C 936-A

Chrysler 68044345EA

Mitsubishi Dia Queen SSTF-I (MZ320065)

Volvo 1161838 / 1161839

VW G 052 182 (DQ 250 / DQ 500)

VW G 052 529 (DL 501)

Technical data	Unit	Test according	DEX-TECH ATF DSG
density at 15°C	Kg/m ³	DIN EN ISO 12185	855
Flammable COC	°C	DIN ISO 2592	224
Pourpoint	°C	DIN ISO 3016	-50
Viskosität 40°C	mm ² /s	DIN 51562-1	35
Viskosität 100°C	mm ² /s	DIN 51562-1	7,0
VI		DIN ISO 2909	170

The expiration date is 2 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.



powered by **Quality.**

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany
Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international registered trademark of **PROFI-TECH GmbH**



powered by **Quality.**

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany
Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international registered trademark of **PROFI-TECH GmbH**