



## HYDRO-TECH HLP 10

HYDRO-TECH HLP 10 is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients.

### Specification

DIN 51524 Teil 2  
FZG-Test A 8,3/90 12

### Recommended application

ISO 11158  
ASTM D6158  
SIS SS 155434  
SAE MS 1004  
GM LS 2  
JCMAS P041 HK  
AIST 127+136  
Denison Filterability TP 02100

Technical data	Unit	Test according	HYDRO-TECH HLP 10
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	854
Flammable COC	°C	DIN ISO 2592	170
Pourpoint	°C	DIN ISO 3016	-33
Viskosität 40°C	mm <sup>2</sup> /s	DIN 51562-1	9,7
Viskosität 100°C	mm <sup>2</sup> /s	DIN 51562-1	2,7
VI		DIN ISO 2909	98

The given data are typical data. Please observe instructions.

powered by **Quality.**

**PROFI-TECH GmbH** • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany  
Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international registered trademark of **PROFI-TECH GmbH**

