

## EUROLUB KÜHLERSCHUTZ D-65

**Produkteigenschaften:  
Anwendung:**

KÜHLERSCHUTZ D-65 is an antifreeze based on ethylene glycol. It contains an inhibitor package based on silicate and OAT. It is free of nitrite, amine and borate. Radiator protection D-65 must be diluted with water before use.

KÜHLERSCHUTZ D-65 is used when BMW LC-18 or VW TL 774-L (G12evo) is required.

KÜHLERSCHUTZ D-65 reduces inventory as it is equally compatible with modern as well as older vehicles. Use your owner's manual to find the correct coolant specification.

KÜHLERSCHUTZ D-65 can be used in BMW models built after 1998 (LC-87).

KÜHLERSCHUTZ D-65 can be used in VW models from 1996 onwards (G12+, G12++, G13).

Since the special application advantages of KÜHLERSCHUTZ D-65, such as good aluminum protection and longer intervals, are only achieved when KÜHLERSCHUTZ D-65 is used alone, mixing with other radiator protection agents is not recommended.

**Can be used for:**

VW TL 774 Ausf. L  
BMW LC-18  
Volvo Cars

VW TL 774 Ausf. C/D/F/G/J  
BMW LC-87  
Deutz CC-14  
AS 2108-2004  
ASTM D-3306, ASTM D-4985, ASTM D-6210  
CUNA NC 956-16  
BS 6580:2010  
JIS K 2234:2006  
PN-C40007:2000  
SAE J1034  
SANS 1251:2005  
GB 29743-2013

# PRODUCT INFORMATION



<b>Delivery:</b>	Art.-Nr. 835015	12 x 1,5 Liter	plastic bottle
	Art.-Nr. 835005	4 x 5 Liter	plastic can
	Art.-Nr. 835020	20 Liter	plastic can
	Art.-Nr. 835060	60 Liter	hobbock
	Art.-Nr. 835208	208 Liter	drum
	Art.-Nr. 835100	1.000 Liter	IBC

## Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.