

EUROLUB ZH-L HYDRAULIK-FLUID

Description/Applications:	EUROLUB ZH-L HYDRAULIK-FLUID has been developed specifically for use in central hydraulic systems, power steering systems, sun roof mechanisms, hydro-pneumatic suspension systems and shock absorbers. Its first-rate viscosity-temperature behaviour guarantees safe operation at high steady-state temperatures, as well as a sensitive response at very low temperatures. Color: brown
----------------------------------	---

Can be used with:	DIN 51524-T3 MB 343.0	ISO 7308
	BMW 54 34 0 394 395 MB 000989 910310	

Delivery:	Art.-Nr. 544001	12 x 1 Liter	bottle
	Art.-Nr. 544020	20 Liter	can
	Art.-Nr. 544060	60 Liter	hobbock
	Art.-Nr. 544208	208 Liter	drum
	Art.-Nr. 544100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB ZH-L HYDRAULIK- FLUID
Density at 15°C	kg/L	D 4052	0,870
Viscosity at 40°C	cSt	D 445	21,0
Viscosity at 100°C	cSt	D 445	6,2
Viscosityindex (VI)		D 2270	280
Flash point (COC)	°C	D 92	130
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 31.05.2021, made: 08.02.2018
	Referenz: R30502, 171017
	Name: 544xxx_TDS_EN
	Seite 1 von 1