

EUROLUB GEAR FLUIDE 17 BM

Description / Applications:	<p>GEAR FLUIDE 17 BM is a high-performance ATF with reduced viscosity on the latest additives. It is specially designed for the newest Mercedes-Benz 9-speed-automatic. The reduced viscosity and the excellent viscosity-temperature behavior enable a reduction in consumption and consequently a decrease on CO₂ emission Can't be used for older MB-automatic gears.</p> <p>Colour: yellow</p>
------------------------------------	---

Can be used with:	<p>MB 236.17 MB 236.16</p>
	<p>MB 002 989 06 03</p>

Delivery:	<p>Art.-Nr. 387001 12 x 1 Liter bottle Art.-Nr. 387020 20 Liter can Art.-Nr. 387060 60 Liter hobbock Art.-Nr. 387208 208 Liter drum Art.-Nr. 387100 Container IBC</p>
------------------	---

Technical Data:			
Data	Unit	Method	EUROLUB Gear FLUIDE 17 BM
Density at 15°C	kg/L	D 4052	0,835
Viscosity at 40°C	cSt	D 445	17,1
Viscosity at 100°C	cSt	D 445	4,23
Viscosityindex (VI)		D 2270	161
Flash point (COC)	°C	D 92	174
Pourpoint	°C	D 6892	-57

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 22.09.2020, erstellt am 22.11.2011
	Referenz: st-a.21.06, 12.04.2018
	Name: 387xxx_TDS_EN
	Seite 1 von 1