

EUROLUB HLP 68

Category:	HLP Hydraulic Fluids
------------------	----------------------

Product Features: application:	The HLP hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures.
---	--

Recommendations:	DIN 51 524 / part 2 FZG-Test A8, 3/90 load stage: 12 ISO 11158 ASTM D 6158 JCMAS P041 HK	ISO VG 68 AIST 127 + 136 SAE MS 1004 GM LS 2
-------------------------	--	---

Delivery:	Art.-Nr. 506020 Art.-Nr. 506060 Art.-Nr. 506208 Art.-Nr. 506100	20 Liter 60 Liter 208 Liter Container	plastic-canister hobbock Drum 800 – 3.000 Liter per destination
------------------	--	--	--

Technical Data:			
Data	Unit	Method	EUROLUB HLP 68
Density at 15°C	kg/L	ASTM D 4052	0,883
Viscosity at 40°C	cSt	ASTM D 445	68,0
Viscosity at 100°C	cSt	ASTM D 445	8,7
Viscosityindex (VI)		ASTM D 2270	99
Flash point (COC)	°C	ASTM D 92	250
Pourpoint	°C	ASTM D 6892	-24

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	print: 24.08.2020, made 28.11.2018
	Referenz: SwioHS, 01.02.2018
	Name: 506xxx_TDS_EN
	Seite 1 von 1