

EUROLUB Kühlerschutz D-30

Description/Applications:	<p>Kühlerschutz D-30 gives outstanding protection against frost, corrosion and overheating in all modern engines, but especially highly loaded aluminium engines. It effectively protects against corrosion and deposits in the cooling system with its vital parts, the coolant channels in the block and cylinder head, the radiator, the water pump and the heatercore.</p> <p>Kühlerschutz D-30 must be diluted with water before use. It is hard water compatible and can be mixed with tap water(*) before filling into the cooling system to give solutions in the concentration range of 30 to 50 % by volume.</p> <p>(*)= For preparation of the coolant use clean, not overly hard water. Waste water from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.</p>
----------------------------------	---

Can be used with:	<p>VW TL 774 Aus. F (D/F) MB 325.3 MAN 324 Typ SNF DAF 74002 Renault 41-01-001 AFNOR NF R15-601 AS 2108 ASTM D3306 ASTM D4656 ASTM D4985 BS 6580 CUNA NC 956-16 FVV Heft R443 SAE J 1034 UNE 26361-88</p>
--------------------------	---

Delivery:	<table> <tr> <td>Art.-Nr. 821015</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 821005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 821020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 821060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 821208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 821100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 821015	12 x 1 Liter	bottle	Art.-Nr. 821005	4 x 5 Liter	can	Art.-Nr. 821020	20 Liter	can	Art.-Nr. 821060	60 Liter	hobbock	Art.-Nr. 821208	208 Liter	drum	Art.-Nr. 821100	Container	IBC
Art.-Nr. 821015	12 x 1 Liter	bottle																	
Art.-Nr. 821005	4 x 5 Liter	can																	
Art.-Nr. 821020	20 Liter	can																	
Art.-Nr. 821060	60 Liter	hobbock																	
Art.-Nr. 821208	208 Liter	drum																	
Art.-Nr. 821100	Container	IBC																	

PRODUCT INFORMATION



Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.