

## EUROLUB GT-N 10W/40

<b>Description/Applications:</b>	<p>This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p> <ul style="list-style-type: none"> <li>- a high and stable viscosity index</li> <li>- a fast cold start</li> <li>- a strong resistance against oxidation</li> <li>- a good detergency and dispersion</li> <li>- a safe lubrication film at high temperatures</li> <li>- a strong protection against wear, corrosion and foaming</li> </ul>
----------------------------------	---

<b>Can be used with:</b>	<p>API SN / CF ACEA A3/B4 MB 229.1 VW 505 00</p>
--------------------------	--

<b>Delivery:</b>	Art.-Nr. 339001	12 x 1 Liter	bottle [for request]
	Art.-Nr. 339005	4 x 5 Liter	can [for request]
	Art.-Nr. 339020	20 Liter	canister
	Art.-Nr. 339060	60 Liter	hobbock
	Art.-Nr. 339208	208 Liter	drum
	Art.-Nr. 339100	Container	IBC 1.000L

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB GT-N 10W/40</b>
Density at 15°C	kg/L	ASTM D 4052	0,867
Viscosity at 40°C	cSt	ASTM D 445	90,4
Viscosity at 100°C	cSt	ASTM D 445	14,1
Viscosityindex (VI)		ASTM D 2270	161
Flash point (COC)	°C	ASTM D 92	226
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. 0049/8165 / 95 91 – 0, Fax 0049/8165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print:18.10.2017, made: 18.10.2017
	reference: R20259, 12.10.2017
	name: GT-N SAE 10W-40 PDS_GB
	page 1 of 1