

EUROLUB SUPERTEC 5W-20

Description / Applications:	SUPERTEC 5W-20 is a fuel saving oil based on synthetic base oils specially developed for the Ford Ecoboost gasoline. This SAE 5W-20 engine oil can also be used were an ACEA C5 or API SN product is recommended.
------------------------------------	---

Can be used with:	ACEA C5 API SN Ford WSS-M2C948-B Jaguar Land Rover STJLR.03.5004
--------------------------	---

Delivery:	Art.-Nr. 314001	12 x 1 Liter	bottle
	Art.-Nr. 314004	4 x 4 Liter	can
	Art.-Nr. 314005	4 x 5 Liter	can
	Art.-Nr. 314020	20 Liter	can
	Art.-Nr. 314060	60 Liter	hobbock
	Art.-Nr. 314208	208 Liter	drum
	Art.-Nr. 314100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB SUPERTEC 5W-20
Density at 15°C	kg/L	D 4052	0,851
Viscosity at 40°C	cSt	D 445	45,4
Viscosity at 100°C	cSt	D 445	8,4
Viscosityindex (VI)		D 2270	162
Flash point (COC)	°C	D 92	232
Pourpoint	°C	D 6892	-38

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 10.08.2021, made 26.04.2018
	Referenz: R20206, 30.08.2019
	Name: 314xxx_TDS_EN
	Seite 1 von 1