

EUROLUB HD 4 CX PLUS 15W-40

Description/Applications:	<p>Universal engine oil designed to meet the latest specifications of heavy diesel engines. This oil is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines). It is not suitable for Euro IV engines with particulate filter. It provides excellent protection against deposits in pipes and turbo engine, an improved protection against camshaft wear and it allows very long drain intervals. This oil can be used for all modern diesel engines of trucks, off-road equipment and other heavy material. It can also be used for all other types of vehicles and cars.</p>
----------------------------------	---

Can be used with:	<p>ACEA A3 / B4, E7 API CI-4/SL MB 229.1 / 228.3 Deutz III-10 Volvo VDS-3 Mack EO-N, EO-M plus JASO DH-1 Caterpillar ECF-2, ECF 1a Cummins CES 20076 / 20077 / 20078</p>	<p>MAN M 3275-1 MTU Type 2 Renault RLD-2 Allison C4 Global DHD-1 Detroit Diesel DDC 93K215</p>
--------------------------	--	---

Delivery:	<p>Art.-Nr. 327020 20 Liter can Art.-Nr. 327060 60 Liter hobbock Art.-Nr. 327208 208 Liter drum Art.-Nr. 327100 Container IBC</p>
------------------	--

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB HD 4CX PLUS 15W-40
Density at 15°C	kg/L	D 4052	0,880
Viscosity at 40°C	cSt	D 445	104
Viscosity at 100°C	cSt	D 445	14,0
Viscosityindex (VI)		D 2270	136
Flash point (COC)	°C	D 92	230
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.