

EUROLUB WIV ECO 5W-30

Description/Applications:



This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III oils.

Can be used with:

ACEA C3
API SN
VW 504.00 / 507.00
MB 229.51
BMW Longlife-04
Porsche C30

Delivery:

Art.-Nr. 211001	12 x 1 Liter	bottle
Art.-Nr. 211004	4 x 4 Liter	can
Art.-Nr. 211005	4 x 5 Liter	can
Art.-Nr. 211020	20 Liter	can
Art.-Nr. 211060	60 Liter	hobbock
Art.-Nr. 211208	208 Liter	drum
Art.-Nr. 211100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB WIV ECO 5W-30
Density at 15°C	kg/L	D 4052	0,848
Viscosity at 40°C	cSt	D 445	69,47
Viscosity at 100°C	cSt	D 445	11,82
Viscosityindex (VI)		D 2270	167
Flash point (COC)	°C	D 92	232
Pourpoint	°C	D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.