



## Xtra-SHIFT 6HP

Xtra-SHIFT 6HP was especially developed for modern ZF 6-speed automatic transmissions and is compatible with older ZF 5-speed automatic transmissions.

This ATF guarantees highest quality, high load carrying capability and extremely low friction properties. The superior friction characteristics, no foaming and lowest evaporation loss are proofs of premium quality.

Observe manufacturer instructions!

### Specification

#### Recommended application

BMW ATF M 1375.4, Hyundai SP-IV

VW / Audi G 055 005 A1/A2/A6

Bentley Oil PY112995PA

Ford MERCON SP/LV

Jaguar Fluid 8432

Land Rover TYK 500050

Maserati Oil 231603, Nissan Matic S

Toyota Type WS

ZF Lifeguardfluid6 (S671 090 255)

Technical data	Unit	Test according	Xtra-SHIFT 6HP
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	853
Flammable COC	°C	DIN ISO 2592	>170
Pourpoint	°C	DIN ISO 3016	-42
Viskosität 40°C	mm <sup>2</sup> /s	DIN 51562-1	31
Viskosität 100°C	mm <sup>2</sup> /s	DIN 51562-1	6,1
VI		DIN ISO 2909	154

The expiration date is 2 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.



powered by **Quality.**

**PROFI-TECH GmbH** • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany  
Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)

**PROFI-CAR** is a international registered trademark of **PROFI-TECH GmbH**