

EUROLUB GEAR FLUIDE V-FE

Description / Applications:

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- red coloured

Can be used with:

AISIN WARNER JWS 3309
JASO M315 Type 1A
JATCO ATF
JATCO 3100 PL085
Toyota ATF Type T/T-II/T-III/T-IV
Nissan/INFINITI MATIC D/J/K
Mitsubishi Diamond SP-II/SP-III
Mazda ATF-M III / ATF-MV
Daihatsu Alumix ATF MULTI
Honda ATF-Z1 (not for CVT) / ATF DW-1
Suzuki 3313, 3317, 2384K
Suzuki ATF OIL / ATF OIL SPECIAL
Subaru ATF / ATF-HP
Hyundai/Kia SP-II/SP-III
GM Dexron IID/IIH
Chrysler ATF +3/+4
VW G052 025-A2 / G052 162-A1 / G 052 990-A1 / G055 025-A1/A2
BMW 7045E / ETL-8072B / LA2634 / LT71141
MB 236.1/2/3/5/6/7/9/10/11
Porsche JWS 3309
Volvo 97340/97341
VOITH 55.6335
Allison C-4
ZF TE-ML 03D/04D/11B/14A/14B/16L/17
Ford MERCON V
MAN 339F/V1/V2/Z1/Z2

PRODUCT INFORMATION



Delivery:	Art.-Nr. 379001	12 x 1 Liter	bottle
	Art.-Nr. 379020	20 Liter	plastic canister
	Art.-Nr. 379060	60 Liter	hobbock
	Art.-Nr. 379208	208 Liter	drum
	Art.-Nr. 379100	Container	800 – 3.000 Liter per destination

Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE V-FE
Density at 15°C	kg/L	ASTM D 4052	0,844
Viscosity at 40°C	cSt	ASTM D 445	31,23
Viscosity at 100°C	cSt	ASTM D 445	6,87
Viscosity index (VI)		ASTM D 2270	189
Flash point (COC)	°C	ASTM D 92	216
Pourpoint	°C	ASTM D 6892	-48

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.