

EUROLUB Gear Fluide AS

Description / Applications:	Gear Fluide AS may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.
------------------------------------	--

Can be used with:	Dexron IIIH Mercon/Mercon V Allison C-4 MAN 339 Type V1/V2/Z11/Z2/Z3 MB 235.71 MB 236.6/8/9/10/11/91 Voith 55.6335/55.6336 Aisin Warner JWS 3309/3314 Allison TES 295/TES 389 BMW LA-2334/LT-71141/ETL 7045 E Chrysler ATF +3/+4 Ford M2C195-A/202-B/922-A1/924-A/938-A GM 9986195 Honda Z1 Hyundai/Kia/Mitsubishi SP-II/III Toyota T-IV/JWS 3309 Volvo 97341/Volvo 5-Speed VW 50160/TL 52 162/ G052 990/ G055 025 ZF 04D/02F/11B/14B/14C/16L/16R/17C/20B/25B
--------------------------	---

Delivery:	Art.-Nr. 371001	12 x 1 Liter	bottle
	Art.-Nr. 371020	20 Liter	can
	Art.-Nr. 371060	60 Liter	hobbock
	Art.-Nr. 371208	208 Liter	drum
	Art.-Nr. 371100	1000 Liter	IBC

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide AS
Density at 15°C	kg/L	ASTM D 4052	0,850
Viscosity at 40°C	cSt	ASTM D 445	34,0
Viscosity at 100°C	cSt	ASTM D 445	7,2
Viscosityindex (VI)		ASTM D 2270	185
Flash point (COC)	°C	ASTM D 92	195
Pourpoint	°C	ASTM D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.