



## EVOLUTION GEAR SAE 75W-90 GL4

EVOLUTION GEAR SAE 75W-90 GL4 is a semi-synthetic low-viscosity gear oil for manual transmissions and normally-loaded axle drives. EVOLUTION GEAR SAE 75W-90 GL4 possesses various advantages compared to conventional gear oils:

Outstanding cold drivability

Excellent thermal stability

Exalted coefficient of viscosity

Sublime shear stability

Avoidance of cold-scraping and effective noise dampening

Excellent corrosion protection

Reduction of fuel consumption

Elongation of oil change intervals

Low abrasion and thus elongated transmission lifespan

Use instructions: EVOLUTION GEAR SAE 75W-90 GL4 is used to lubricate normally-loaded axle drives with low offsets, as well as in synchronized and non-synchronized manual transmissions, and in steering and transfer gears in automotive and processing machines.

### Specification

API GL-4

### Recommended application

MB 235.1 / 235.11

MAN 341 Z-1

ZF TE-ML 02A, 16A, 17A, 19A

Technical data	Unit	Test according	EVOLUTION GEAR SAE 75W-90 GL4
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	875
Flammable COC	°C	DIN ISO 2592	234
Pourpoint	°C	DIN ISO 3016	-45
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	82,30
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	14,47
VI		DIN ISO 2909	184

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**