



SYNTH-TECH FS SAE 5W-40

SYNTH-TECH FS SAE 5W-40 is a motor oil for the fuel efficient and economical operation of motors. To guarantee the performance of the SAE 5W class together with low volatility SYNTH-TECH FS SAE 5W-40 consists entirely of synthetic base oils which meet the high technological demands of the latest motor generation.

SYNTH-TECH FS SAE 5W-40 is an all-season, fuel efficient motor oil. It is especially developed for all modern cars with fuel or diesel motors likewise for turbocharged motors as well as cars with catalysts.

Specification

API SN/CF, ACEA A3/B4, JASO MA2

Recommended application

MB 229.3

Porsche A40

BMW Longlife – 01

Renault RN 0700/ RN 0710

VW-Norm 502 00/ 505 00

GM-LL-B-025 (obsolete)

Technical data	Unit	Test according	SYNTH-TECH FS SAE 5W-40
density at 15°C	Kg/m ³	DIN EN ISO 12185	857
Flammable COC	°C	DIN ISO 2592	232
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm ² /s	DIN 51562-1	88,0
Viscosity 100°C	mm ² /s	DIN 51562-1	14,5
VI		DIN ISO 2909	173
TBN	mgKOH/g	DIN ISO 3771	10,2

The expiration date is 2 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.



powered by **Quality.**

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany
 Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international registered trademark of **PROFI-TECH GmbH**