

EUROLUB GEAR FLUIDE 14 BM

Description/Applications:	High Performance-ATF specially designed for Mercedes-Benz—7-gear-automatic. Obey instructions in the manual. Colour: red
----------------------------------	--

Can be used with:	MB 236.12 MB 236. 14 Hyundai/Kia Red-1K SSANG YONG
	MB 001 989 68 03 MB 001 989 77 03

Delivery:	Art.-Nr. 382001	12 x 1 Liter	bottle
	Art.-Nr. 382020	20 Liter	canister
	Art.-Nr. 382060	60 Liter	hobbock
	Art.-Nr. 382208	208 Liter	drum
	Art.-Nr. 382100	Container	IBC 1.000L

Technical Data:			
Data	Unit	Method	EUROLUB GEAR FLUIDE 14 BM
Density at 15°C	kg/L	ASTM D 4052	0,841
Viscosity at 40°C	cSt	ASTM D 445	32,7
Viscosity at 100°C	cSt	ASTM D 445	6,5
Viscosityindex (VI)		ASTM D 2270	157
Flash point (COC)	°C	ASTM D 92	224
Pourpoint	°C	ASTM D 6892	-44

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 22.09.2020, made: 28.11.2018
	reference: R25050, 01.11.2015
	name: 382xxx_TDS_EN
	page 1 of 1