



DEX-TECH PCUdT ULTIMATE ATF

DEX-TECH PCUdT ULTIMATE ATF is a Automatic Transmission Fluid with the following properties:

- Extremely high viscosity index
- High load capacity, outstanding wear minimisation
- Low pour point
- No foaming
- High thermal stability
- Reliable friction coefficient characteristic
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

Use instructions:

- Automatic motor vehicle transmissions and torque converters
- Hydrostatic transmissions
- Power steering systems
- Hydraulic systems
- Observe manufacturer instructions!
- Colour: not coloured

Specification

Recommended application

- General Motors Dexron III-H
- MB 236.1 / 236.5 / 236.6 / 236.7
- MAN 339 Typ Z1/V1
- Ford Mercon
- Allison C-4
- Cat TO-2
- Voith H55.6335.3x(G607)
- Volvo 97341
- ZF TE-ML 03D/0 4D/09/11/14A/17C

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**



Technical data	Unit	Test according	DEX-TECH PCUDT ULTIMATE ATF
density at 15°C	Kg/m ³	DIN EN ISO 12185	860
Flammable COC	°C	DIN ISO 2592	176
Pourpoint	°C	DIN ISO 3016	-48
Viscosity 40°C	mm ² /s	DIN 51562-1	36
Viscosity 100°C	mm ² /s	DIN 51562-1	7,5
VI		DIN ISO 2909	176

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**